


# **Dual-Frequency GNSS Receiver**





- Vanguard Technology™
- Universal Tracking Technology
- Rugged, Magnesium Alloy Construction
- Integrated RTK and Static Receiver
- Fence Antenna<sup>™</sup> Advanced Performance

## **HiPer V** Dual-Frequency GNSS Receiver

# Compact, cable-free solution with Vanguard Technology for all GNSS positioning applications.

Topcon enhances the HiPer family of products by adding Vanguard Technology to the HiPer V. In the early 2000's Topcon revolutionized GNSS receivers by integrating the design to be compact and light weight. Topcon continues the revolution with Vanguard Technology™.

Topcon raises the standard once again by adding Vanguard Technology with 226 channels, Universal Tracking Technology, and the Fence Antenna into the versatile and configurable HiPer V. Universal Tracking Technology is an advanced firmware process that allows each of the 226 channels to be assigned to any satellite signal.

## **GPS, GLONASS, and Galileo Signal Tracking**

The HiPer V is capable of tracking GPS, GLONASS, and Galileo signals. The recent addition of Galileo E1 band of signals will provide better performance in difficult environments such as urban canyons and forested areas.

#### **Internal Radio Configurations**

The HiPer V can be configured with the radio and cellular modem that best fits your needs. You can choose from Digital UHF or Spread Spectrum radio. Further, you can choose from HSPA, CDMA, or no cellular module. If you start your HiPer V investment with static only receivers, they can later be upgraded to include radio and cellular modules at one of many Topcon service facilities around the globe.



#### **Integrated Radio and Modem Choice**

- Spread Spectrum Radio
- Digital UHF II Radio
- HSPA Cellular Modem
- CDMA Modem



## **Rugged Design**

- Magnesium metal housing
- Drop-proof
- Durable, rugged
- Waterproof



#### **Integrated GPS, GLONASS, Galileo**

- USA based GPS satellites
- Russian based GLONASS satellites
- European based Galileo satellites



### **Housing Features**

- External power port
- External serial port
- Tape measure hook
- Shock protected ring



The HiPer V is designed rugged enough to perform in a real jobsite. It is also waterproof IP67, which means it can be submersed into water. The ports, speaker and battery door are all completely sealed from dust and water.



## **Voice Alerts**

Voice status messages keep you informed without having to look at the screen of the field controller, or the status lights above your head. Stay safe in traffic situations by looking at oncoming traffic rather than looking for the word "Fixed".








## Fence Antenna™ Technology

This superior GNSS antenna element is light-weight, rugged, and sensitive enough to track signals in environments where other receivers fail. Obtain lock sooner, and track longer with Fence Antenna™ technology.



## KIT COMPONENTS BASE AND ROVER

## **System Components**

- 2x HiPer V Receivers
- 4x Batteries, 2x Chargers and Cables
- Radio Antenna
- Carrying Case
- 10cm Spacer and 3m Tape Measure
- Tribrach and Adapter w/Optical Plummet





#### **SPECIFICATIONS**

Capabilities

Number of Channels 226 Channels with Universal

Tracking Technology L1 CA, L1/L2 P-code, L2C

Tracked Signals GPS L1 CA, L1/L2 P-code, L2 GLONASS L1/L2 CA, L1/L2 P-code

Galileo E1\*

SBAS WAAS, EGNOS, MSAS, QZSS

#### **Positioning Accuracy**

Static L1+L2

H: 3mm + 0.5ppm V: 5mm + 0.5ppm

L1 only H: 3mm + 0.8ppm

V: 4mm + 1ppm

RTK, Kinematic L1+L2 H: 10mm + 1ppm V: 15mm + 1ppm

<0.5m

#### **Wireless Communication**

Bluetooth® V2.1 + EDR, Class 2,115,200bps
Radio UHF, Spread Spectrum,

Cellular (options)

#### **Environmental**

**DGPS** 

Dust/Water Protection IP67

Shock 6.56 ft. (2m) pole drop

Operating Temperature

Battery

Cellular

External Power -40°F to +149°F

(-40°C to +65°C)

-4°F to +149°F (-20°C to +65°C)

-4° to +131°F

(-20° to +55°C)

#### Physical

Weight

Enclosure Magnesium alloy housing Size 7.24" D x 3.74" H

(184mm D x 95mm H) HiPer V receiver 2.20 lb. to

2.82 lb. (1.0kg to 1.28kg)

Battery (BDC70) 7.23 oz. (195g)

#### **Power Supply**

Standard Battery Detachable, Li-ion rechargeable

battery, 7.2V, 4.3Ah

Operating Time >7.5 hours in static mode at 68°F (20°C) w/Bluetooth® connection

External Power Input Voltage 6.7 to 18V DC

For more specifications information: www.topcon-positioning.eu

#### SOFTWARE

## MACNET

A family of software solutions that streamlines the workflow for surveyors, contractors, engineers and mapping professionals.

#### **MAGNET Field**

MAGNET Field provides a bright, graphical user interface with large touch icons and bright readable text. Select your color scheme Black, Gold, Blue, Silver, for your best visibility.





© 2013 Google Map Data

## **MAGNET Enterprise**

A managers dream of tracking all field and office data in one simple to access web interface. Store and exchange your field data in the Enterprise cloud.

#### **MAGNET Office**

Full CAD functionality with MAGNET Office Site and Topo. Or field data processing with MAGNET Office Tools inside AutoCAD® products, like Civil3D®. The MAGNET Office solution has what you need.



Гост применим к геодезическому оборудованию и приборам.

# **TOPCON**

#### topcon.eu

Topcon Europe Positioning, B.V • Essebaan 11 • 2908 LJ - Capelle a/d IJssel • The Netherlands (+31) 10 4585077

Specifications subject to change without notice. ©2013 Topcon Corporation All rights reserved. P/N: T722EN Rev. A TF

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

Your local Authorized Topcon dealer is:

<sup>\*</sup> Support for Galileo will be available via option file upgrade when the constellation is fully operational and ready for commercial use.