

Leica Geosystems GNSS Comparison Chart



	Leica GS18 I	Leica GS18 T	Leica GS16	Leica GS07	Leica GS10	Leica GS25
Signal tracking	Multi-frequency	Multi-frequency	Multi-frequency	Multi-frequency	Multi-frequency	Multi-frequency
GPS / GLONASS / Galileo / BeiDou / QZSS / SBAS	✓ / ✓ / ✓ / ✓ / ✓ / ✓	✓ / ✓ / ✓ / ✓ / ✓ / ✓	✓ / ✓ / ✓ / ✓ / ✓ / ✓	✓ / ✓ / ✓ / ✓ / ✓ / ✓	✓ / ✓ / ✓ / ✓ / ✓ / ✓	✓ / ✓ / ✓ / ✓ / ✓ / ✓
SmartLink fill / SmartLink	✓ / ✓	✓ / ✓	✓ / ✓	X / X	✓ / ✓	✓ / ✓
Imaging functionality	✓	X	X	X	X	X
Tilt compensation	✓	✓	X	X	X	X
Single baseline RTK	Hz 8 mm + 1 ppm / V 15 mm + 1 ppm	Hz 8 mm + 1 ppm / V 15 mm + 1 ppm	Hz 8 mm + 1 ppm / V 15 mm + 1 ppm	Hz 10 mm + 1 ppm / V 20 mm + 1 ppm	Hz 8 mm + 1 ppm / V 15 mm + 1 ppm	Hz 8 mm + 1 ppm / V 15 mm + 1 ppm
Network RTK	Hz 8 mm + 0.5 ppm / V 15 mm + 0.5 ppm	Hz 8 mm + 0.5 ppm / V 15 mm + 0.5 ppm	Hz 8 mm + 0.5 ppm / V 15 mm + 0.5 ppm	Hz 10 mm + 0.5 ppm / V 20 mm + 0.5 ppm	Hz 8 mm + 0.5 ppm / V 15 mm + 0.5 ppm	Hz 8 mm + 0.5 ppm / V 15 mm + 0.5 ppm
Static (phase) with long observations	Hz 3 mm + 0.1 ppm / V 3.5 mm + 0.4 ppm	Hz 3 mm + 0.1 ppm / V 3.5 mm + 0.4 ppm	Hz 3 mm + 0.1 ppm / V 3.5 mm + 0.4 ppm	Hz 3 mm + 0.5 ppm / V 6 mm + 0.5 ppm	Hz 3 mm + 0.1 ppm / V 3.5 mm + 0.4 ppm	Hz 3 mm + 0.1 ppm / V 3.5 mm + 0.4 ppm
Static and rapid static (phase)	Hz 3 mm + 0.5 ppm / V 5 mm + 0.5 ppm	Hz 3 mm + 0.5 ppm / V 5 mm + 0.5 ppm	Hz 3 mm + 0.5 ppm / V 5 mm + 0.5 ppm	Hz 5 mm + 0.5 ppm / V 10 mm + 0.5 ppm	Hz 3 mm + 0.5 ppm / V 5 mm + 0.5 ppm	Hz 3 mm + 0.5 ppm / V 5 mm + 0.5 ppm
Reliability	99.99%	99.99%	99.99%	99.95%	99.99%	99.99%
5 Hz / 20 Hz positioning	✓ / ✓	✓ / ✓	✓ / ✓	✓ / ✓	✓ / ✓	✓ / ✓
Raw data / RINEX data logging / NMEA out	✓ / ✓ / ✓	✓ / ✓ / ✓	✓ / ✓ / ✓	✓ / ✓ / X	✓ / ✓ / ✓	✓ / ✓ / ✓
RTK reference station functionality	✓	✓	✓	X	✓	✓
Cellular / UHF radio (receive & transmit) modem	4G / ✓	4G / ✓	3G / ✓	Controller internal / Receive only	3G / ✓	3G / ✓
Storage	SD card	SD card	Micro SD card	Controller internal	SD card	SD card
User interface (buttons / LEDs / display)	2 / 8 / X	2 / 8 / X	2 / 7 / X	1 / 3 / X	2 / 7 / X	7 / 7 / ✓
Power, Bluetooth®, USB, RS232	✓	✓	✓	✓	✓	✓
Event and PPS	X	X	X	X	X	✓
Operating temperature	-30°C to +50°C (camera active) -40°C to +65°C (camera inactive)	-40°C to +65°C	-40°C to +65°C	-40°C to +65°C	-40°C to +65°C	-40°C to +65°C
IP68 proof against water, sand and dust	✓	✓	✓	✓	✓	✓
Weight (without battery)	1.25 kg	1.20 kg	0.93 kg	0.70 kg	1.20 kg	1.84 kg
Operating time with internal UHF radio (Rx / Tx)	7 h / 5 h	7 h / 5 h	7 h / 5 h	7 h / NA (device in controller)	15 h / 13 h	14 h / 12 h
Operating time with internal phone	6 h	6 h	6 h	7 h (device in controller)	14 h	13 h

✓ = Standard X = Not available

Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. – 2020.
Leica Geosystems AG is part of Hexagon AB. 02.20

Гост применим к геодезическому оборудованию и приборам.

leica-geosystems.com



- when it has to be **right**

Leica
Geosystems

